

[54] FOLDABLE ELECTRONIC APPARATUS

[75] Inventors: Hideo Fushimoto; Shigeru Toyomura, both of Kawasaki; Yoshiaki Nishimuro, Hachiohji; Osamu Asakura; Masahiro Rachi, both of Tokyo, all of Japan

[73] Assignee: Canon Kabushiki Kaisha, Tokyo, Japan

[21] Appl. No.: 490,550

[22] Filed: May 6, 1983

Related U.S. Application Data

[63] Continuation of Ser. No. 244,258, Mar. 16, 1981, abandoned.

[30] Foreign Application Priority Data

Mar. 27, 1980 [JP] Japan 55-39249
May 14, 1980 [JP] Japan 55-62750

[51] Int. Cl.³ G06C 7/02; G06F 3/02

[52] U.S. Cl. 364/708; 200/5 A;
340/365 R; 340/365 S; 364/709

[58] Field of Search 364/708, 709;
340/365 R, 365 S; 200/5 A, 159 B

[56] References Cited

U.S. PATENT DOCUMENTS

3,772,597	11/1973	Stover	340/365 S X
3,940,758	2/1976	Margolin	364/708 X
4,075,702	2/1978	Davies	364/705
4,096,577	6/1978	Ferber et al.	364/708 X
4,117,542	9/1978	Klausner et al.	364/900
4,324,976	4/1982	Lapeyre	340/365 R X
4,395,704	7/1983	Kishimoto et al.	340/365 S

Primary Examiner—Jerry Smith

Assistant Examiner—Clark A. Jablon

Attorney, Agent, or Firm—Fitzpatrick, Cella, Harper & Scinto

[57] ABSTRACT

An electronic apparatus comprises a left-hand unit and a right-hand unit mutually connected to constitute a foldable structure, in which a display device is provided in one of the units while an aperture is provided in the other to enable observation of the display device even in the folded state of the apparatus. Operational keys are provided on the other unit or on both units to enable operation of the apparatus in the open and/or folded position thereof.

7 Claims, 7 Drawing Figures

